









---

# Determination of gamma ray shielding parameters of rocks and concrete

Shamsan S. Obaid , Dhammajyot K. Gaikwad  , Pravina P. Pawar 

Show more 

 Share  Cite

---

<https://doi.org/10.1016/j.radphyschem.2017.09.022> 

[Get rights and content](#) 

---

## Highlights

- Gamma-ray shielding properties of rocks and concrete have been studied.
- Feldspathic basalt is a good candidate for gamma shielding applications.
- Gamma-ray shielding properties of concrete can be improved with the addition of basalt rock.

## Abstract

Gamma shielding parameters such as mass attenuation coefficient ( $\mu/\rho$ ), effective atomic number ( $Z_{\text{eff}}$ ) and electron density ( $N_{\text{eff}}$ ) have been measured and calculated for rocks and concrete in the energy range 122–1330 keV. The measurements have been carried out at 122, 356, 511, 662, 1170, 1275, 1330 keV gamma ray energies using a gamma spectrometer includes a NaI(Tl) scintillation detector and MCA card. The atomic and electronic cross sections have also been investigated. Experimental and calculated (WinXCom) values were compared, and good agreement has been observed within the experimental error. The obtained results showed that feldspathic basalt,

compact basalt, volcanic rock, dolerite and pink granite are more efficient than the sandstone and concrete for gamma ray shielding applications.

---

## Introduction

Study of the interaction of gamma radiations with matter is an important subject in the field of nuclear medicine, diagnostics, radiation protection and radiation physics and chemistry. The probability of radiation interacting with a material per unit path length is called the linear attenuation coefficient ( $\mu$ ), and is of great importance in radiation shielding. The mass attenuation coefficient ( $\mu/\rho$ ), which is defined as the  $\mu$  per unit mass of the material, is the basic physical quantity characterizing the diffusion and penetration gamma radiations in the materials. Scattering and absorption of gamma radiations are related to the density and atomic numbers of the material, therefore knowledge of ( $\mu/\rho$ ), atomic cross section ( $\sigma_t$ ), electronic cross section ( $\sigma_{el}$ ),  $Z_{eff}$  and  $N_{eff}$  are of prime importance. The glass, concrete and rock are used in the radiation shielding technology because of its high attenuation cross-section for X-rays, Gamma ray photons and neutrons (Abdo, 2002, Singh et al., 2008). Typical applications of these materials are in the construction of hospitals (X-ray unit and therapy room), nuclear research laboratories, power stations, particle accelerators and radioactive waste disposal units.

Investigation of the physical parameters such as ( $\mu/\rho$ ),  $\sigma_t$ ,  $\sigma_{el}$ ,  $Z_{eff}$  and  $N_{eff}$  of rocks and concretes is useful for understanding their physical properties. A comparison of predicted and experimental values of attenuation coefficients provides a check on the validity of physical parameters such as X-ray emission rates, fluorescence yields and jump ratio (Sitamahalakshmi et al., 2015). In composite materials, a single number cannot represent the atomic number uniquely in the entire energy region for photon interactions. This unique number for complex materials is called  $Z_{eff}$ , which is varying with energy. The effective atomic number is a convenient parameter for understanding the attenuation of X-rays and gamma photons in composites (Manohara et al., 2007). The accurate value of  $Z_{eff}$  is very useful for medical radiation dosimetry, imaging and technological applications.

Nowadays, radiations and radioisotopes are used in many diverse fields such as medical diagnosis, medicine, nuclear and food industry, scientific research. Therefore gamma ray shielding investigation of various material gains great attention. Tabulations of ( $\mu/\rho$ ) and the mass energy absorption coefficients for 40 elements and 45 mixtures and some compounds over the energy range from 1 keV to 20MeV have been reported by Hubbell (1982). Chantler published tabulations of scattering cross-sections and quantities related to ( $\mu/\rho$ ). A computer program XCOM was developed by the Berger and Hubbell (1987), which calculates attenuation coefficients and photon cross sections for elements compounds and mixtures in the energy range 1 keV to 100GeV. This widely used program transformed to windows platform called WinXCOM (Gerward, 2001). Using XCOM and WinXCOM, many attempts have been made to calculate attenuation coefficients for different elements, compounds and mixtures. Kaewkhao et al. (2010) determined the ( $\mu/\rho$ )

experimentally and theoretically for borate-bismuth glass system. Un and Demir (2013) calculated ( $\mu/\rho$ ),  $Z_{\text{eff}}$  and  $N_{\text{eff}}$  of heavy-weight and normal-weight concrete, and observed that iron, barium and calcium concentration of the concretes is more capable for X- or gamma radiation shielding. Demir and Keles (2006) performed a narrow beam transmission experiment using Am-241 and Ba-133 for concrete containing boron waste, and found out that ( $\mu/\rho$ ) is increased with increasing boron concentration in the concrete. Medhat (2009) determined the ( $\mu/\rho$ ) for the building materials using a high-resolution HPGe spectrometer detector, and showed that a brick covered with cement can shield about 49–67% more radiations than brick itself. In recent years, A great number of researchers reported ( $\mu/\rho$ ),  $Z_{\text{eff}}$  and  $N_{\text{eff}}$  in different materials such as concretes (Akkurt et al., 2012, Medhat, 2012, Oto et al., 2015, Oto et al., 2016), alloys (Singh et al., 2014, Kaewkhaoa et al., 2008), compound and mixtures (Awasarmol et al., 2017a, Awasarmol et al., 2017b; Bhosale et al., 2016a, 2016b; Gaikwad et al., 2016; Pawar and Bichile, 2013; Un and Sahin, 2011) and glasses (Matori et al., 2017, Singh et al., 2014). Oto et al. (2016) calculated  $Z_{\text{eff}}$  and effective removal cross-sections of magnetite concrete for gamma and fast neutron shielding.

In this paper, mass attenuation coefficients ( $\mu/\rho$ ) of some rocks and a concrete have been measured in the energy range 122–1330keV and calculated using the computer code WinXCom. Then atomic and electronic cross sections, effective atomic number and electron density have been determined using ( $\mu/\rho$ ) for same energies. This work also includes a comparison of attenuation coefficients of rocks with concrete. Present results could be very useful in radiation shielding applications for construction of nuclear power plants, X-ray and radiotherapy units.

---

## Section snippets

### Experimental details

Concrete has been produced using the ordinary Portland cement (PC 42.5) and normal sand. A constant water (w) to cement (c) ratio ( $w/c = 50\%$ ) and 25% normal sand concentration was selected for concrete preparation. Rocks and produced concrete samples were ground separately and sieved with 400 mesh. These samples were heated (at 60°C) in a muffle furnace for 48h. The chemical contents of the concrete and rock samples were measured by X- ray fluorescence spectrometer (XRF, SPECTRO XEPOS, AMETEK), ...

### Results and discussions

The chemical composition of a concrete and the rock samples used in this work are given in Table 1. The values of ( $\mu/\rho$ ) for the rocks and a concrete have been measured at gamma energies from 122 to 1330keV and calculated using WinXCom, are shown in Table 2. Fig. 2 shows the trends of measured ( $\mu/\rho$ ) values for all samples at photon energies from 122 to 1330keV. It is clearly seen from this

figure that  $(\mu/\rho)$  depends on the gamma-ray energy. It is obviously seen from Fig. 2 that the values of...

## Conclusion

Gamma rays shielding properties of the rocks and concrete have been studied. Results of the  $(\mu/\rho)$ ,  $\sigma_t$  and  $\sigma_{el}$  increase with decreasing incident gamma ray energy. It is noticed that  $Z_{eff}$  and  $N_{eff}$  depend on elements of the materials and incoming photon energies. The mass attenuation coefficient of feldspathic basalt, compact basalt, volcanic rock, dolerite and pink granite is higher than sandstone and concrete. This means that the feldspathic basalt, compact basalt, volcanic rock, dolerite and...

## Acknowledgement

One of the authors DKG would like to thank University Grant Commission, New Delhi for providing RGNF...

[Recommended articles](#)

---

## References (28)

I. Akkurt *et al.*

[Chemical corrosion on gamma ray attenuation properties of barite concrete](#)

J. Saud. Chem. Soc. (2012)

V.V. Awasarmol *et al.*

[Photon interaction study of organic nonlinear optical materials in the energy range 122–1330keV](#)

Radiat. Phys. Chem. (2017)

Demet Demir *et al.*

[Radiation transmission of concrete including boron waste for 59.54 and 80.99 keV gamma rays](#)

Nucl. Instrum. Methods Phys. Res. B. (2006)

D.K. Gaikwad *et al.*

[Mass attenuation coefficients and effective atomic numbers of biological compounds for gamma ray interactions](#)

Radiat. Phys. Chem. (2017)

L. Gerward *et al.*

### X-ray absorption in matter

Reengineering Xcom. Radiat. Phys. Chem. (2001)

J.H. Hubbell

### Photon mass attenuation and energy-absorption

Int. J. Appl. Radiat. Isot. (1982)

J. Kaewkhao *et al.*

### Study on borate glass system containing with Bi<sub>2</sub>O<sub>3</sub> and BaO for gamma-rays shielding materials: comarison with PbO

J. Nucl. Mater. (2010)

S.R. Manohara *et al.*

### Studies on effective atomic numbers and electron densities of essential amino acids in the energy range 1 keV–100 GeV

Nucl. Instrum. Methods Phys. Res. Sect. B (2007)

K.A. Matori *et al.*

### Comprehensive study on physical, elastic and shielding properties of lead zinc phosphate glasses

J. Non-Cryst. Solids (2017)

M.E. Medhat

### Gamma-ray attenuation coefficients of some building materials available in Egypt

Ann. Nucl. Energy (2009)



View more references

---

## Cited by (221)

### Structural, mechanical, and radiation shielding properties of B<sub>2</sub>O<sub>3</sub>–Na<sub>2</sub>O–PbO–Fe<sub>2</sub>O<sub>3</sub> glass system

2024, Radiation Physics and Chemistry

Show abstract

### IMUPF-BIN: A new autonomous search method for radioactive sources

2024, Progress in Nuclear Energy

[Show abstract](#) 

## Investigation of nano MgO loaded polyvinyl chloride polymer in protective clothing as a nonlead materials

2024, Heliyon

[Show abstract](#) 

## Novel starch–tungsten (VI) oxide biocomposites: Preparation, characterization, and comparisons between experimental and theoretical photon attenuation coefficients

2024, International Journal of Biological Macromolecules

[Show abstract](#) 

## Impacts of siltstone rocks on the ordinary concrete's physical, mechanical and gamma-ray shielding properties: An experimental examination

2024, Nuclear Engineering and Technology

[Show abstract](#) 

## Physical and $\gamma$ -ray shielding properties of Vietnam's natural stones: An extensive experimental and theoretical study

2024, Nuclear Engineering and Technology

[Show abstract](#) 



[View all citing articles on Scopus](#) 

---

[View full text](#)

© 2017 Elsevier Ltd. All rights reserved.



All content on this site: Copyright © 2024 Elsevier B.V., its licensors, and contributors. All rights are reserved, including those for text and data mining, AI training, and similar technologies. For all open access content, the Creative Commons licensing terms apply.

